

## 6.6A 64322 30W EXLDL 12/CS 1/SKU



### Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

### Areas of application

- Airfield Lighting

# Product datasheet

## Technical data

### General Product Information

Global order reference	64322
Product number (Americas)	58850
Product name (Americas)	6.6A 64322 30W EXLDL 12/CS 1/SKU
Lamp type	SINGLE ENDED
ANSI code	EXL


### Electrical Data

Nominal wattage	30 W
Nominal current	6.6 A
Type of current	AC

### Photometric Data

Nominal luminous flux	400 lm
Color temperature	2950 K
Color rendering index Ra	100
Light center length (LCL)	25.4 mm
Light center length (LCL) - (in)	1 in

### Physical Attributes & Dimensions



Lamp base	GY9.5
Diameter (in)	0.453 in
Diameter	13.5 mm
Length	44.5 mm
Product weight	10.42 g

### Operating Conditions

## Product datasheet

<b>Burning position</b>	s90 <sup>1)</sup>
-------------------------	-------------------

<sup>1)</sup> Despite transverse filament, can be inclined at any angle in s90 position

### Lifetime Data

<b>Nominal lifetime</b>	1500 hr
-------------------------	---------

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
<b>Primary article identifier</b>	4008321100146
<b>Date of declaration</b>	22-09-2024
<b>Declaration no. in SCIP database</b>	In work
<b>Candidate list substance 1</b>	No declarable substances contained

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58850	4008321100146	FOLDING BOX	1	1.7 in x 1.7 in x 4.4 in	0.1 lb
58850	4008321100153	SHIPPING BOX	12	7.1 in x 5.5 in x 5 in	0.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.