

## LOKIT 1000/PS BRILLIANT 10/CS 1/SKU



### Product features and benefits

- Compact design and short arc gap allows for smaller and brighter fixtures
- Fast lamp replacement with one-touch rotate and lock base and socket design
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Power series offers enhanced performance features and versatility, including BRILLIANT lamps with high CRI and BLUE lamps that offer 7500K for bright white light

### Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

# Product datasheet

## Technical data

### General Product Information

Global order reference	Lok-it! 1000/PS Brilliant
Product number (Americas)	55024
Product name (Americas)	LOKIT 1000/PS BRILLIANT 10/CS 1/SKU
Family brand	Lok-it!

### Electrical Data

Nominal wattage	1000 W
Nominal voltage	85.0 V
Nominal current	11.8 A

### Photometric Data

Nominal luminous flux	82000 lm
Color temperature	6000 K
Color rendering index Ra	95
Light center length (LCL)	56.0 mm

### Physical Attributes & Dimensions

Electrode gap (cold)	5.5 mm
Lamp base	-
Diameter	28.0 mm
Length	112.5 mm
Product weight	57.00 g

### Lifetime Data

Nominal lifetime	750 hr
------------------	--------

### Environmental & Regulatory Information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
Primary article identifier	4052899568266   4052899965164
Date of declaration	22-09-2024
Declaration no. in SCIP database	In work
Candidate list substance 1	No declarable substances contained

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
55024	4052899965164	SHIPPING BOX	1	7.2 in x 3.4 in x 2.3 in	0.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.