

## XBO 1000W/HSC 1/CS 1/SKU



### Product features and benefits

- High luminance (point source)
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart
- Long lamp life with eXtreme Life technology

### Areas of application

- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

# Product datasheet

## Technical data

### General Product Information

Global order reference	XBO 1000 W/HSC OFR
Product number (Americas)	69264
Product name (Americas)	XBO 1000W/HSC 1/CS 1/SKU
Lamp type	XENON
Product remark	OFR = Ozone-free version/H = Suitable for horizontal burning position/S = Short/C= Base with cable

### Electrical Data


Nominal wattage	1000 W
Nominal current	50 A
Current control range	30...55 A

### Photometric Data

Luminance	60000 cd/cm <sup>2</sup> <sup>1)</sup>
Nominal luminous flux	32000 lm
Color temperature	6000 K
Color rendering index Ra	98
Light center length (LCL)	95.0 mm

<sup>1)</sup> Measured in the vertical burning position

### Physical Attributes & Dimensions



Electrode gap (cold)	3.6 mm
Base (anode)	SK27/50
Base (cathode)	SFcX27-8
Diameter (in)	1.575 in
Diameter	40.0 mm

## Product datasheet

Length	236.0 mm
Length with base excl. base pins/connection	220.00 mm
Connector: presence	Yes
Product weight	303.00 g

### Operating Conditions

Burning position	s20/p20 <sup>1)</sup>
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

<sup>1)</sup> For vertical burning position: anode (+) on top

### Lifetime Data

Nominal lifetime	1500 hr
Warranty hours	2000 hrs

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321082107
Date of declaration	22-09-2024
Declaration no. in SCIP database	f094a128-1489-4dbf-8649-bb523f769078
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69264	4008321082107	SHIPPING BOX	1	16.1 in x 7.2 in x 7.1 in	1.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.