

## XBO 3000W/DHS 1/CS 1/SKU



### Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

### Areas of application

- Digital Cinema Projection

# Product datasheet

## Technical data

### General Product Information

Global order reference	XBO 3000 W/DHS OFR
Product number (Americas)	69462
Product name (Americas)	XBO 3000W/DHS 1/CS 1/SKU


### Electrical Data

Nominal wattage	3000 W
Nominal voltage	29.0 V
Nominal current	105 A
Current control range	77...113 A
Type of current	DC

### Photometric Data

Nominal luminous flux	130000 lm
Light center length (LCL)	145.0 mm

### Physical Attributes & Dimensions



Electrode gap (cold)	6.0 mm
Base (anode)	SFaX27-9.5
Base (cathode)	SFa27-7.9
Diameter (in)	2.126 in
Diameter	60.0 mm
Length	342.0 mm
Length with base excl. base pins/connection	302.00 mm
Cable/wire length, input side	155 mm
Connector: presence	Yes
Product weight	591.00 g

## Product datasheet

### Operating Conditions

Burning position	s15/p15 <sup>1)</sup>
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

<sup>1)</sup> For vertical burning position: anode (+) on top

### Lifetime Data

Nominal lifetime	1500 hr
Warranty hours	1500 hrs
Service warranty lifetime	2000 hr

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321199065   4062172030540   4008321330017
Date of declaration	14-10-2024
Declaration no. in SCIP database	0ad1e6ac-a107-4e86-a73c-0a8cdc49edb4 468df0c2-2da9-47b4-a001-357079e3d0c0
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	Die Bezeichnung des Stoffes der Kandidatenliste reicht aus für den sicheren Gebrauch des Produktes.

### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69462	4062172030540	SHIPPING BOX	1	19.7 in x 8 in x 8 in	3.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.