

XBO 6500W/DHP XL 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Cinema Projection

Product datasheet

Technical data

General Product Information

Global order reference	XBO 6500 W/DHP XL OFR
Product number (Americas)	55225
Product name (Americas)	XBO 6500W/DHP XL 1/CS 1/SKU

Electrical Data

Nominal wattage	6500 W
Nominal voltage	39.0 V
Nominal current	165 A
Current control range	133...173 A

Photometric Data

Light center length (LCL)	170.5 mm
---------------------------	----------

Physical Attributes & Dimensions

Electrode gap (cold)	8.0 mm
Base (anode)	SFaX30-9.5
Base (cathode)	SFa30-7.9
Diameter	78.0 mm
Length	436.0 mm
Length with base excl. base pins/connection	393.00 mm
Cable/wire length, input side	155 mm
Connector: presence	Yes
Product weight	1023.00 g

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	900 hr
Warranty hours	800 hrs
Service warranty lifetime	1000 hr

Environmental & Regulatory Information

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899593640 4062172031684
Date of declaration	14-10-2024
Declaration no. in SCIP database	0afbcf5a-721a-4942-bd3d-6024b2eff6a3
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	Die Bezeichnung des Stoffes der Kandidatenliste reicht aus für den sicheren Gebrauch des Produktes.

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
55225	4062172031684	SHIPPING BOX	1	23.2 in x 9.2 in x 9.2 in	4.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.