

XBO 3000W/DTP 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Cinema Projection

Product datasheet

Technical data

General Product Information

Global order reference	XBO 3000 W/DTP OFR
Product number (Americas)	69154
Product name (Americas)	XBO 3000W/DTP 1/CS 1/SKU


Electrical Data

Nominal wattage	3000 W
Nominal voltage	31.0 V
Nominal current	101 A
Current control range	74...109 A
Type of current	DC

Photometric Data

Nominal luminous flux	130000 lm
Light center length (LCL)	160.0 mm

Physical Attributes & Dimensions



Electrode gap (cold)	6.0 mm
Base (anode)	SFa30-14
Base (cathode)	SFc30-14
Diameter (in)	2.362 in
Diameter	60.0 mm
Length	397.0 mm
Length with base excl. base pins/connection	354.00 mm
Product weight	536.00 g

Operating Conditions

Product datasheet

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	1500 hr
Warranty hours	1500 hrs
Service warranty lifetime	2500 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321191540 4052899509474
Date of declaration	14-10-2024
Declaration no. in SCIP database	cdf74e98-4a09-4bdf-8cd1-2fd9bd8791fb
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	Die Bezeichnung des Stoffes der Kandidatenliste reicht aus für den sicheren Gebrauch des Produktes.

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69154	4052899509474	SHIPPING BOX	1	23.2 in x 9.2 in x 9.2 in	3.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.