

XBO 6000W/HPN L 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Cinema Projection

Product datasheet

Technical data

General Product Information

Global order reference	XBO 6000 W/HPN L OFR
Product number (Americas)	69054
Product name (Americas)	XBO 6000W/HPN L 1/CS 1/SKU


Electrical Data

Nominal wattage	6000 W
Nominal voltage	39.0 V
Nominal current	156 A
Current control range	125...158 A
Type of current	DC

Photometric Data

Nominal luminous flux	300000 lm
Light center length (LCL)	171.5 mm

Physical Attributes & Dimensions



Electrode gap (cold)	8.0 mm
Base (anode)	SFaX30-9.5
Base (cathode)	SFa30-20
Diameter	78.0 mm
Length	428.0 mm
Length with base excl. base pins/connection	389.00 mm
Cable/wire length, input side	235 mm
Connector: presence	Yes
Product weight	1015.00 g

Product datasheet

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	1000 hr
Warranty hours	800 hrs
Service warranty lifetime	1200 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172111171 4052899343412 4062172030687
Date of declaration	22-09-2024
Declaration no. in SCIP database	2c9d4d2e-189b-4cd8-8946-603008b0d3df
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69054	4062172030687	SHIPPING BOX	1	23.2 in x 9.2 in x 9.2 in	5.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.