

XBO 2000W/HPS L 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Cinema Projection

Product datasheet

Technical data

General Product Information

Global order reference	XBO 2000 W/HPS L OFR
Product number (Americas)	68883
Product name (Americas)	XBO 2000W/HPS L 1/CS 1/SKU


Electrical Data

Nominal wattage	2000 W
Nominal voltage	25.0 V
Nominal current	82 A
Current control range	46...87 A
Type of current	DC

Photometric Data

Nominal luminous flux	80000 lm
Light center length (LCL)	128.0 mm

Physical Attributes & Dimensions



Electrode gap (cold)	4.5 mm
Base (anode)	SFaX30-14/68
Base (cathode)	SFc30-20/50
Diameter	55.0 mm
Length	334.0 mm
Length with base excl. base pins/connection	297.00 mm
Cable/wire length, input side	195 mm
Connector: presence	Yes
Product weight	595.10 g

Product datasheet

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	3000 hr
Warranty hours	3000 hrs
Service warranty lifetime	3500 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172030342 4052899287761
Date of declaration	30-09-2024
Declaration no. in SCIP database	c816075e-2194-4118-a481-54224e3feee4
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
68883	4062172030342	SHIPPING BOX	1	19.7 in x 8 in x 8 in	3.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.