

64647 120W 24V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54320
Product Name	64647 120W 24V 40/CS 1/SKU
Application	Projector, Microfilm, Microscope, Studio
LIF Code	M/184

Electrical data

Nominal Wattage	120 W
Nominal Voltage	22.8 V
Type of Current	AC

Light technical data

Luminous Flux	3600 lm
Light Center Length - LCL (in)	1.18 in
Light Center Length - LCL (mm)	30 mm
Color Rendering Index	100
Average Rated Life	1000 h


Physical attributes

Base	G6.35
Bulb Shape	T12
Maximum Overall Length (in)	1.73 in
Maximum Overall Length (mm)	44 mm
Length l (in)	1.73 in
Length l (mm)	44 mm
Distance a (in)	0.510 in
Distance a (mm)	30 mm
Filament Dimensions Length (in)	0.1000 in
Filament Dimensions Length (mm)	2.6 mm
Filament Dimensions Width (in)	0.25 in
Filament Dimensions Width (mm)	6.4 mm

Additional product data

Operating Position	s 90
Class	C (gas)
Lamp Type	SINGLE END

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54320	4008321107114	Folding box (SKU)	1	1 in x 0.9 in x 2.8 in	
54320	4008321107121	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.