

220T4Q/2PPF220W22V GY9.5



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	58939
Product Name	220T4Q2PPF220W22VGY9.5 12/CS 1/SKU
Ordering Abbreviation	220T4Q/2PPF220W22V GY9.5
Brand Name	OSRAM
General Description	220 watt, tungsten halogen, low voltage without reflector
Application	Medical Overhead Illumination

Electrical data

Nominal Wattage	220 W
Nominal Voltage	22 V
Type of Current	AC

Light technical data

Luminous Flux	6200 lm
Light Center Length - LCL (in)	1.525 in
Light Center Length - LCL (mm)	39.1 mm
Color Temperature	3250 K
Color Rendering Index	100
Average Rated Life	200 h

Physical attributes

Base	GY9.5 BIPIN
Bulb Shape	T12
Maximum Overall Length (in)	2.574 in
Maximum Overall Length (mm)	66 mm
Length l (in)	2.574 in
Length l (mm)	66 mm
Length l max. (in)	2.574 in
Length l max. (mm)	66 mm
Diameter d (in)	0.500 in
Diameter d (mm)	12.70 mm
Distance a (in)	1.525 in
Distance a (mm)	39.1 mm
Filament	CC-6

Product datasheet

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	Clear
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
58939	0046135589393	Folding box (SKU)	1		
58939	10046135589390	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.