

## 20PAR/36/CAP/WFL



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	55052
Product Name	20PAR36CAPWFL 12V 12/CS 1/SKU
Ordering Abbreviation	20PAR/36/CAP/WFL
Brand Name	OSRAM
General Description	Tungsten Halogen Capsylite Par36 Screw terminal & spade connector Base20W 12V Wide Flood Beam
Application	Landscaping
Product Remark	- WFL=Wide Flood

#### Electrical data

Nominal Wattage	20 W
Nominal Voltage	12 V

#### Light technical data

Beam Angle (degree)	25
Centerbeam Candlepower (cp)	550
Color Rendering Index	100
Average Rated Life	4000 h

#### Physical attributes

Base	Screw Terminal G53
Bulb Shape	PAR36
Maximum Overall Length (in)	2.75 in
Maximum Overall Length (mm)	69.850 mm
Length l (in)	2.75 in
Length l (mm)	69.850 mm
Diameter d (in)	4.500 in
Diameter d (mm)	114.30 mm
Filament	C-8

#### Additional product data

Operating Position	Any
Class	C (gas)
Lamp Type	PAR36

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
55052	4008321470737	Folding box (SKU)	1	3.5 in x 3.5 in x 4.1 in	0.6 lb
55052	4008321470744	Shipping box (Case)	12	14.7 in x 11.1 in x 4.9 in	7.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.