

8018 15W 6V 100/CS 1/SKU



Product features and benefits

- Dependable quality
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	76314
Product Name	8018 15W 6V 100/CS 1/SKU
Application	Projector
LIF Code	M/20
Product Remark	<ul style="list-style-type: none">- Lamp has a flat core filament with filament area perpendicular to the lamp axis.- h (Operating Position) = Vertical, base up

Electrical data

Nominal Wattage	15 W
Nominal Voltage	6 V
Type of Current	AC


Physical attributes

Base	B15D DOUBLE CONTACT BAYONET
Maximum Overall Length (in)	2.028 in
Maximum Overall Length (mm)	52 mm
Length l (in)	2.028 in
Length l (mm)	52 mm
Length l max. (in)	2.028 in
Length l max. (mm)	52 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	0.195 in
Distance a (mm)	5 mm
Filament Dimensions Length (in)	0.0740 in
Filament Dimensions Length (mm)	1.9 mm
Filament Dimensions Width (in)	0.059 in
Filament Dimensions Width (mm)	1.5 mm

Additional product data

Operating Position	h 30
Class	C (gas)

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
76314	4050300206417	Folding box (SKU)	1	1 in x 1 in x 2.7 in	
76314	4050300206424	Shipping box (Case)	100	10.6 in x 5.6 in x 6.1 in	3.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.