

## HTI 250 W/32 2/CS 1/SKU



### Product features and benefits

- Robust design with precision reflector alignment
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

### Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

# Product datasheet

## Technical data

### General product information

|                   |   |
|-------------------|---|
| Product Number    | 54081   |
| Product Name      | HTI 250 W/32 2/CS 1/SKU   |
| Family Brand Name | HTI   |
| Application       | Entertainment and Effect Lighting, Fiber Optic  |
| Product Remark    | <ul style="list-style-type: none"><li>- p (Operating Position) = Horizontal</li><li>- Lamp is also available with connecting cable and plug-in contact. HTI 250W/32 C (Product Number 54089).</li></ul> |

### Electrical data

|                 |       |
|-----------------|-------|
| Nominal Wattage | 250 W |
| Nominal Voltage | 45 V  |
| Current (A)     | 6 A   |
| Type of Current | AC    |

### Light technical data

|                         |        |
|-------------------------|--------|
| Working Distance a (mm) | 32 mm  |
| Color Temperature       | 5600 K |
| Color Rendering Index   | 70     |
| Average Rated Life      | 250 h  |


### Physical attributes

|                             |                                |
|-----------------------------|--------------------------------|
| Base                        | LEADS WITH AMP 350809-1 CONNEC |
| Bulb Shape                  | REFLECTOR                      |
| Maximum Overall Length (mm) | 73 mm                          |
| Length l (mm)               | 73 mm                          |
| Length l max. (mm)          | 73 mm                          |
| Diameter d (in)             | 2.638 in                       |
| Diameter d (mm)             | 67.00 mm                       |
| Electrode Gap - cold (mm)   | 2.5 mm                         |

### Additional product data

|                               |        |
|-------------------------------|--------|
| Operating Position            | P 20   |
| Maximum Base Temperature (°C) | 230 C  |
| Cooling                       | Forced |
| Hot Restart                   | Yes    |

## Product datasheet



### Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54081          | 4050300226576 | Folding box (SKU)   | 1        | 3.4 in x 3.4 in x 4.1 in     | 0.3 lb       |
| 54081          | 4050300226583 | Shipping box (Case) | 2        | 7.3 in x 3.8 in x 4.5 in     | 0.7 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.