

HMI DIGITAL 4000W 1/CS 1/SKU



Product features and benefits

- Reduced flicker when used with high-speed electronic ballasts (up to 1000 Hz and higher)
- Suited for both analog and digital film productions
- High intensity light providing true color performance with a CRI>90
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- High energy efficiency providing up to 100 LPW
- Enhanced safety with UV-Stop (UVS) feature on all DIGITAL types

Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Product datasheet

Technical data

General product information

| | |
|-------------------|------------------------------|
| Product Number | 55081 |
| Product Name | HMI DIGITAL 4000W 1/CS 1/SKU |
| Family Brand Name | HMI DIGITAL |

Electrical data

| | |
|-----------------|--------|
| Nominal Wattage | 4000 W |
| Nominal Voltage | 200 V |

Light technical data

| | |
|-----------------------|-----------|
| Luminous Flux | 387000 lm |
| Color Temperature | 6000 K |
| Color Rendering Index | 90 |
| Average Rated Life | 500 h |

Physical attributes

| | |
|------------|-------|
| Base | G38 |
| Bulb Shape | GST75 |

Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions L x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 55081 | 4052899984301 | Shipping box (Case) | 1 | 13.5 in x 6 in x 5.7 in | 1.3 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.