

DPY 120V



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Technical data

General product information

Product Number	54554
Product Name	DPY120V 6/CS 1/SKU
Ordering Abbreviation	DPY 120V
Brand Name	OSRAM
General Description	5000W 120 volt, DPY, Tungsten Halogen, G38 base
Application	STAGE & STUDIO
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	5000 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	143000 lm
Light Center Length - LCL (in)	6.435 in
Light Center Length - LCL (mm)	165 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	500 h

Physical attributes

Base	G38 Mogul Bipost
Bulb Shape	T19
Maximum Overall Length (in)	10.842 in
Maximum Overall Length (mm)	278 mm
Length l (in)	10.842 in
Length l (mm)	278 mm
Diameter d (in)	2.362 in
Diameter d (mm)	60.00 mm
Distance a (in)	6.435 in
Distance a (mm)	165 mm
Filament	C13
Filament Dimensions Length (in)	1.0200 in
Filament Dimensions Length (mm)	26 mm
Filament Dimensions Width (in)	1.42 in

Product datasheet

Filament Dimensions Width (mm)	36 mm
Reflector Coating	60.00

Additional product data

Operating Position	S45
Class	C (GAS)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54554	4052899129580	Folding box (SKU)	1	13.3 in x 5.4 in x 5.6 in	1.3 lb
54554	4008321893628	Shipping box (Case)	6	16.6 in x 11.7 in x 13.7 in	7.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.