

## HPL 375/115/X (UCF)



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Technical data

### General product information

|                       |   |
|-----------------------|---|
| Product Number        | 54649   |
| Product Name          | HPL375115X (UCF)115V 12/CS 1/SKU                  |
| Ordering Abbreviation | HPL 375/115/X (UCF)                               |
| Brand Name            | OSRAM   |
| Family Brand Name     | HPL   |
| General Description   | 375 watt, tungsten halogen, HPL series, long life |
| Application           | Stage & Studio                                    |

### Electrical data

|                 |       |
|-----------------|-------|
| Nominal Wattage | 375 W |
| Nominal Voltage | 115 V |
| Type of Current | AC    |

### Light technical data

|                                |          |
|--------------------------------|----------|
| Luminous Flux                  | 8000 lm  |
| Light Center Length - LCL (in) | 2.352 in |
| Light Center Length - LCL (mm) | 60.3 mm  |
| Color Temperature              | 2950 K   |
| Color Rendering Index          | 100      |
| Average Rated Life             | 1000 h   |

### Physical attributes

|                             |                     |
|-----------------------------|---------------------|
| Base                        | G9.5 with Heat Sink |
| Bulb Shape                  | T8                  |
| Maximum Overall Length (in) | 4.1 in              |
| Maximum Overall Length (mm) | 104 mm              |
| Length l (in)               | 4.1 in              |
| Length l (mm)               | 104 mm              |
| Length l max. (in)          | 4.1 in              |
| Length l max. (mm)          | 104 mm              |
| Diameter d (in)             | 0.748 in            |
| Diameter d (mm)             | 19.00 mm            |
| Distance a (in)             | 2.352 in            |
| Distance a (mm)             | 60.3 mm             |
| Filament                    | 4-C8                |
| Reflector Coating           | 19.00               |

## Product datasheet

### Additional product data

|  |            |
|--|------------|
| <b>Operating Position</b>                        | Any        |
| <b>Total surface inside 1: appearance (cold)</b> | Clear      |
| <b>Class</b>                                     | C (gas)    |
| <b>Lamp Type</b>                                 | SINGLE END |

### Packaging Information

| Product number | EAN/UPC        | Packaging           | Quantity | Outside dimensions L x w x h | Gross weight |
|----------------|----------------|---------------------|----------|------------------------------|--------------|
| 54649          | 0046135546495  | Folding box (SKU)   | 1        | 1.6 in x 1.6 in x 5.1 in     | 0.2 lb       |
| 54649          | 10046135546492 | Shipping box (Case) | 12       | 7 in x 5.4 in x 6 in         | 1.8 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.