

## BVT



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54690
Product Name	BVT 120V 6/CS 1/SKU
Ordering Abbreviation	BVT
Brand Name	OSRAM
General Description	1,000 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

#### Electrical data

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

#### Light technical data

Luminous Flux	23000 lm
Light Center Length - LCL (in)	3.9 in
Light Center Length - LCL (mm)	100 mm
Color Temperature	3050 K
Color Rendering Index	100
Average Rated Life	500 h

#### Physical attributes

Base	P40s Mogul Prefocus
Bulb Shape	T7
Maximum Overall Length (in)	6.934 in
Maximum Overall Length (mm)	177.8 mm
Length l (in)	6.934 in
Length l (mm)	177.8 mm
Length l max. (in)	6.934 in
Length l max. (mm)	177.8 mm
Diameter d (in)	0.945 in
Diameter d (mm)	24.00 mm
Distance a (in)	3.900 in
Distance a (mm)	100 mm
Filament	C-13D

## Product datasheet

### Additional product data

<b>Operating Position</b>	Any
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54690	4008321483287	Unpacked (SKU)	1		
54690	10046135546904	Shipping box (Case)	6	11.4 in x 10.5 in x 8.4 in	5.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.