

## BVW



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

|                       |  |
|-----------------------|--|
| Product Number        | 54692  |
| Product Name          | BVW 115V 6/CS 1/SKU  |
| Ordering Abbreviation | BVW  |
| Brand Name            | OSRAM  |
| General Description   | 2,000 watt, tungsten halogen, medium to high voltage, single-ended |
| Application           | Stage & Studio   |

#### Electrical data

|                 |        |
|-----------------|--------|
| Nominal Wattage | 2000 W |
| Nominal Voltage | 120 V  |
| Type of Current | AC     |

#### Light technical data

|                                |          |
|--------------------------------|----------|
| Luminous Flux                  | 59000 lm |
| Light Center Length - LCL (in) | 3.9 in   |
| Light Center Length - LCL (mm) | 100 mm   |
| Color Temperature              | 3200 K   |
| Color Rendering Index          | 100      |
| Average Rated Life             | 280 h    |

#### Physical attributes

|                             |                     |
|-----------------------------|---------------------|
| Base                        | P40s Mogul Prefocus |
| Bulb Shape                  | T9.5                |
| Maximum Overall Length (in) | 7.925 in            |
| Maximum Overall Length (mm) | 203.2 mm            |
| Length l (in)               | 7.925 in            |
| Length l (mm)               | 203.2 mm            |
| Length l max. (in)          | 7.925 in            |
| Length l max. (mm)          | 203.2 mm            |
| Diameter d (in)             | 1.063 in            |
| Diameter d (mm)             | 27.00 mm            |
| Distance a (in)             | 3.900 in            |
| Distance a (mm)             | 100 mm              |

#### Additional product data

---

## Product datasheet

|  |            |
|--|------------|
| <b>Operating Position</b>                        | Any        |
| <b>Total surface inside 1: appearance (cold)</b> | Clear      |
| <b>Class</b>                                     | C (gas)    |
| <b>Lamp Type</b>                                 | SINGLE END |

---

### Packaging Information

| Product number | EAN/UPC        | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|----------------|---------------------|----------|------------------------------|--------------|
| 54692          | 4008321483300  | Unpacked (SKU)      | 1        |                              |              |
| 54692          | 10046135546928 | Shipping box (Case) | 6        | 11.4 in x 10.5 in x 8.4 in   | 5.9 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.