

## GLD 750/115/300



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54522
Product Name	GLD750115300 12/CS 1/SKU
Ordering Abbreviation	GLD 750/115/300
Brand Name	OSRAM
General Description	750 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio
Product Remark	- Lamp has a biplane filament.

#### Electrical data

Nominal Wattage	750 W
Nominal Voltage	115 V
Type of Current	AC

#### Light technical data

Luminous Flux	19000 lm
Light Center Length - LCL (in)	2.359 in
Light Center Length - LCL (mm)	60.5 mm
Color Temperature	3250 K
Average Rated Life	300 h

#### Physical attributes

Base	G9.5 Medium Bipin
Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l1 (in)	4.1 in
Length l1 (mm)	104 mm
Length l1 max. (in)	4.1 in
Length l1 max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.359 in
Distance a (mm)	60.5 mm
Filament	C-13D

## Product datasheet

### Additional product data

<b>Operating Position</b>	Any
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54522	0046135545221	Folding box (SKU)	1		
54522	10046135545228	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.