

---

## HPL 750/120/X (UCF)



---

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

---

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54653
Product Name	HPL750120X (UCF) 120V 12/CS 1/SKU
Ordering Abbreviation	HPL 750/120/X (UCF)
Brand Name	OSRAM
Family Brand Name	HPL
General Description	750 watt, tungsten halogen, HPL series, long life
Application	Stage & Studio

#### Electrical data

Nominal Wattage	750 W
Nominal Voltage	120 V
Type of Current	AC

#### Light technical data

Luminous Flux	16400 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3065 K
Color Rendering Index	100
Average Rated Life	2000 h

#### Physical attributes

Base	G9.5 with Heat Sink
Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	4-C8
Reflector Coating	19.00

## Product datasheet

### Additional product data

<b>Operating Position</b>	Any
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54653	4052899347946	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54653	4052899347953	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.