

## CYV



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

Product Number	54706
Product Name	CYV 120V 6/CS 1/SKU
Ordering Abbreviation	CYV
Brand Name	OSRAM
General Description	1,000 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

#### Electrical data

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

#### Light technical data

Luminous Flux	27500 lm
Light Center Length - LCL (in)	4.953 in
Light Center Length - LCL (mm)	127 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	200 h

#### Physical attributes

Base	G38 Mogul Bipost
Bulb Shape	T7
Maximum Overall Length (in)	7.644 in
Maximum Overall Length (mm)	196 mm
Length l (in)	7.644 in
Length l (mm)	196 mm
Length l max. (in)	7.644 in
Length l max. (mm)	196 mm
Diameter d (in)	0.945 in
Diameter d (mm)	24.00 mm
Distance a (in)	4.953 in
Distance a (mm)	127 mm
Filament	C-13D

## Product datasheet

### Additional product data

<b>Operating Position</b>	Any
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54706	4008321483331	Unpacked (SKU)	1		
54706	10046135547062	Shipping box (Case)	6	11.4 in x 10.5 in x 8.4 in	5.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.