

## CYV



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

|                       |  |
|-----------------------|--|
| Product Number        | 54706  |
| Product Name          | CYV 120V 6/CS 1/SKU  |
| Ordering Abbreviation | CYV  |
| Brand Name            | OSRAM  |
| General Description   | 1,000 watt, tungsten halogen, medium to high voltage, single-ended |
| Application           | Stage & Studio   |

#### Electrical data

|                 |        |
|-----------------|--------|
| Nominal Wattage | 1000 W |
| Nominal Voltage | 120 V  |
| Type of Current | AC     |

#### Light technical data

|                                |          |
|--------------------------------|----------|
| Luminous Flux                  | 27500 lm |
| Light Center Length - LCL (in) | 4.953 in |
| Light Center Length - LCL (mm) | 127 mm   |
| Color Temperature              | 3200 K   |
| Color Rendering Index          | 100      |
| Average Rated Life             | 200 h    |

#### Physical attributes

|                             |                  |
|-----------------------------|------------------|
| Base                        | G38 Mogul Bipost |
| Bulb Shape                  | T7               |
| Maximum Overall Length (in) | 7.644 in         |
| Maximum Overall Length (mm) | 196 mm           |
| Length l (in)               | 7.644 in         |
| Length l (mm)               | 196 mm           |
| Length l max. (in)          | 7.644 in         |
| Length l max. (mm)          | 196 mm           |
| Diameter d (in)             | 0.945 in         |
| Diameter d (mm)             | 24.00 mm         |
| Distance a (in)             | 4.953 in         |
| Distance a (mm)             | 127 mm           |
| Filament                    | C-13D            |

## Product datasheet

### Additional product data

|  |            |
|--|------------|
| <b>Operating Position</b>                        | Any        |
| <b>Total surface inside 1: appearance (cold)</b> | Clear      |
| <b>Class</b>                                     | C (gas)    |
| <b>Lamp Type</b>                                 | SINGLE END |

### Packaging Information

| Product number | EAN/UPC        | Packaging           | Quantity | Outside dimensions L x w x h | Gross weight |
|----------------|----------------|---------------------|----------|------------------------------|--------------|
| 54706          | 4008321483331  | Unpacked (SKU)      | 1        |                              |              |
| 54706          | 10046135547062 | Shipping box (Case) | 6        | 11.4 in x 10.5 in x 8.4 in   | 5.9 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.