

EFX



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54787
Product Name	EFX 120V 12/CS 1/SKU
Ordering Abbreviation	EFX
Brand Name	OSRAM
General Description	500 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio

Electrical data

Nominal Wattage	500 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	10000 lm
Light Center Length - LCL (in)	3.962 in
Light Center Length - LCL (mm)	101.6 mm
Color Temperature	3000 K
Color Rendering Index	100
Average Rated Life	2000 h

Physical attributes

Base	G22 Medium Bipost
Bulb Shape	T5
Maximum Overall Length (in)	6.439 in
Maximum Overall Length (mm)	165.1 mm
Length l (in)	6.439 in
Length l (mm)	165.1 mm
Length l max. (in)	6.439 in
Length l max. (mm)	165.1 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Distance a (in)	3.962 in
Distance a (mm)	101.6 mm
Filament	CC-8

Product datasheet

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	Clear
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54787	0046135547874	Folding box (SKU)	1		
54787	10046135547871	Shipping box (Case)	12	9.8 in x 7.4 in x 8.5 in	3.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.