

HPL 750/77 (UCF)



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54825
Product Name	HPL75077 (UCF) 77V 12/CS 1/SKU
Ordering Abbreviation	HPL 750/77 (UCF)
Brand Name	OSRAM
General Description	750 watt, tungsten halogen, HPL series
Application	Stage & Studio

Electrical data

Nominal Wattage	750 W
Nominal Voltage	77 V
Type of Current	AC

Light technical data

Luminous Flux	22950 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3265 K
Color Rendering Index	100
Average Rated Life	300 h

Physical attributes

Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	4-C8
Reflector Coating	19.00

Additional product data

Product datasheet

Operating Position	Any
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54825	0046135548253	Folding box (SKU)	1		
54825	10046135548250	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.