

1200W 120V GX9.5



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	55035
Product Name	1200W120VGX95 12/CS 1/SKU
Ordering Abbreviation	1200W 120V GX9.5
Brand Name	OSRAM
General Description	Tungsten Halogen, 1200 watt, 120 volt, GX9.5 base, equivalent to the 71-2529, used in the VL5 series
Application	VL5 & VL500 Moving Lights

Electrical data

Nominal Wattage	1200 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	34200 lm
Light Center Length - LCL (in)	2.165 in
Light Center Length - LCL (mm)	55 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	150 h

Physical attributes

Base	GX9.5 Bipin Prefocus
Bulb Shape	T8
Maximum Overall Length (in)	4.331 in
Maximum Overall Length (mm)	110 mm
Diameter d (in)	0.984 in
Diameter d (mm)	25.00 mm
Filament	C-13D
Filament Dimensions Length (in)	0.4650 in
Filament Dimensions Length (mm)	11.8 mm
Filament Dimensions Width (in)	0.59 in
Filament Dimensions Width (mm)	15 mm

Additional product data

Operating Position	Any
--------------------	-----

Product datasheet

Maximum Base Temperature (°C)	350 C
Cooling	Required
Total surface inside 1: appearance (cold)	Clear

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
55035	4052899544307	Folding box (SKU)	1	2.8 in x 2.8 in x 6.3 in	0.2 lb
55035	4052899544314	Shipping box (Case)	12	11.6 in x 8.7 in x 6.9 in	2.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.