

64501 150W 120V 20/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54781
Product Name	64501 150W 120V 20/CS 1/SKU
Application	Stage & Studio

Electrical data

Nominal Wattage	150 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	4500 lm
Light Center Length - LCL (in)	1.17 in
Light Center Length - LCL (mm)	30 mm
Color Temperature	3250 K
Color Rendering Index	100
Average Rated Life	50 h

Physical attributes

Base	GX6.35 BIPIN
Bulb Shape	T12
Maximum Overall Length (in)	2.145 in
Maximum Overall Length (mm)	55 mm
Length l (in)	2.145 in
Length l (mm)	55 mm
Length l max. (in)	2.145 in
Length l max. (mm)	55 mm
Diameter d (in)	0.433 in
Diameter d (mm)	11.00 mm
Distance a (in)	1.170 in
Distance a (mm)	30 mm
Filament Dimensions Length (in)	0.0850 in
Filament Dimensions Length (mm)	2.2 mm
Filament Dimensions Width (in)	0.429 in
Filament Dimensions Width (mm)	11 mm

Additional product data

Product datasheet

Operating Position	Any
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54781	4008321746030	Folding box (SKU)	1	1.3 in x 1.5 in x 2.8 in	
54781	4008321746047	Shipping box (Case)	20	8.1 in x 5.6 in x 3 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.