

FNS 64512



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54764
Product Name	FNS64512 12/CS 1/SKU
Ordering Abbreviation	FNS 64512
Brand Name	OSRAM
General Description	300 WATT, TUNGSTEN HALOGEN, MEDIUM TO HIGH VOLT, SINGLE-ENDED
Application	Projector, Stage & Studio
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	300 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	9800 lm
Light Center Length - LCL (in)	1.053 in
Light Center Length - LCL (mm)	27 mm
Color Temperature	3350 K
Color Rendering Index	100
Average Rated Life	15 h

Physical attributes


Base	GX6.35 Bipin
Bulb Shape	T6
Maximum Overall Length (in)	2.086 in
Maximum Overall Length (mm)	53 mm
Length l (in)	2.086 in
Length l (mm)	53 mm
Length l max. (in)	2.086 in
Length l max. (mm)	53 mm
Diameter d (in)	0.728 in
Diameter d (mm)	18.50 mm
Distance a (in)	1.053 in
Distance a (mm)	27 mm
Filament Dimensions Length (in)	0.4921 in

Product datasheet

Filament Dimensions Length (mm)	12.5 mm
Filament Dimensions Width (in)	0.0393 in
Filament Dimensions Width (mm)	10 mm
Reflector Coating	18.50

Additional product data

Operating Position	s 90
Class	C (gas)



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54764	4008321746115	Folding box (SKU)	1	1.3 in x 1.5 in x 2.9 in	
54764	4008321746122	Shipping box (Case)	20	8.1 in x 5.6 in x 3 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.