

## EVW



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Technical data

### General product information

Product Number	54723
Product Name	EVW 82V 24/CS 1/SKU
Ordering Abbreviation	EVW
Brand Name	OSRAM
General Description	250 watt, tungsten halogen, low to medium voltage with reflector
Application	Projector
Product Remark	- s (Operating Position) = Vertical, base down - Lumens refers to screen lumens.

### Electrical data

Nominal Wattage	250 W
Nominal Voltage	82 V
Type of Current	AC

### Light technical data

Luminous Flux	390 lm
Working Distance a (in)	11.642 in
Working Distance a (mm)	298.5 mm
Color Rendering Index	100
Average Rated Life	50 h

### Physical attributes

Base	GY5.3 Bipin
Bulb Shape	T3.5
Maximum Overall Length (in)	1.755 in
Maximum Overall Length (mm)	45 mm
Length l (in)	1.755 in
Length l (mm)	45 mm
Length l max. (in)	1.755 in
Length l max. (mm)	45 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	CC-8
Reflector Coating	51.00

## Product datasheet

### Additional product data

<b>Operating Position</b>	s 90
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	MR16

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54723	4050300350172	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54723	10046135547239	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.