
FCM 120V



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54442
Product Name	FCM 120V 12/CS 1/SKU
Ordering Abbreviation	FCM 120V
Brand Name	OSRAM
General Description	1,000 watt, tungsten halogen, medium to high voltage, double-ended
Application	Stage & Studio
LIF Code	P2/28
Product Remark	- p (Operating Position) = Horizontal

Electrical data

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	28000 lm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h

Physical attributes

Base	R7s
Bulb Shape	T3
Maximum Overall Length (in)	4.664 in
Maximum Overall Length (mm)	119.6 mm
Length l (in)	4.664 in
Length l (mm)	119.6 mm
Length l max. (in)	4.664 in
Length l max. (mm)	119.6 mm
Filament	C-6

Additional product data

Operating Position	p 4
Total surface inside 1: appearance (cold)	Clear
Class	C (gas)

Product datasheet

Lamp Type	DOUBLE END
------------------	------------

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54442	0046135544422	Folding box (SKU)	1	1.3 in x 1.3 in x 5.5 in	0.2 lb
54442	10046135544429	Shipping box (Case)	12	6.3 in x 5.6 in x 4.5 in	1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.