

G38 NO LEADS 15/CS 1/SKU



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69372
Product Name	G38 NO LEADS 15/CS 1/SKU
Ordering Abbreviation	G38 NO LEADS 15/CS 1/SKU
Old Part Number	F512015

Electrical data

Maximum Wattage (W)	18000 W
Maximum Voltage (V)	1000 V
Voltage - Pulse Rated (kV)	50 kV
Current (A)	50 A

Physical attributes

Length (in)	4 in
Length (mm)	102.5 mm
Width (in)	2.6 in
Width (mm)	65 mm
Height (in)	1.7 in
Height (mm)	42 mm
Body Material	Ceramic Steatite
Contact Material	Nickel Plated Brass
Wire Type	N/A
Wire Gauge (AWG)	6 - 14 AW AWG

Additional product data

Lamp Base Reference	Mogul Bi-Post
Maximum Operating Temperature (°C)	350 C
Rohs Compliant	Yes

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69372	4008321488497	Shipping box (Case)	1	4.9 in x 3.3 in x 2.4 in	1.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.