

TP120 12IN/18GA/ULSF1



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69021
Product Name	TP12012IN18GAULSF1 100/CS 20/SKU
Ordering Abbreviation	TP120 12IN/18GA/ULSF1
Brand Name	OSRAM
General Description	TP120, SOCKET, LAMPHOLDER 12" LEADS
CSA File No.	LR20904

Electrical data

Maximum Wattage (W)	750 W
Maximum Voltage (V)	250 V

Physical attributes

Length (in)	1.07 in
Length (mm)	27.2 mm
Width (in)	0.76 in
Width (mm)	19.2 mm
Height (in)	0.34 in
Height (mm)	8.54 mm
Body Material	Ceramic Steatite
Contact Material	Nickel Alloy
Wire Type	UL SF1
Wire Gauge (AWG)	18 AWG
Wire Color(s)	WHITE
Lead Length (in)	12 in
Lead Length (mm)	305 mm
Lead Strip Length (in)	0.25 in
Lead Strip Length (mm)	6.35 mm

Additional product data

Lamp Base Reference	G5.3, GU5.3, GX5.3, GY5.3
Maximum Operating Temperature (°C)	225 C
Rohs Compliant	yes
Underwriters Laboratories File No.	E31557

Product datasheet

TP120

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69021	10046135690218	Shipping box (Case)	100	14.3 in x 11.1 in x 9.1 in	17.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.