

---

## TP22HCE 165CM16GAUL1659 40/CS 10/SKU



---

### Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

---

### Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

## Product datasheet

### Technical data

#### General product information

|                       |                                      |
|-----------------------|--------------------------------------|
| Product Number        | 69017                                |
| Product Name          | TP22HCE 165CM16GAUL1659 40/CS 10/SKU |
| Ordering Abbreviation | TP22HCE 165CM16GAUL1659 40/CS 10/SKU |
| CSA File No.          | LR20904                              |

#### Electrical data

|                     |        |
|---------------------|--------|
| Maximum Wattage (W) | 1000 W |
| Maximum Voltage (V) | 250 V  |

#### Physical attributes

|                        |                      |
|------------------------|----------------------|
| Length (in)            | 0.75 in              |
| Length (mm)            | 19 mm                |
| Width (in)             | 0.85 in              |
| Width (mm)             | 21.7 mm              |
| Height (in)            | 0.43 in              |
| Height (mm)            | 10.8 mm              |
| Body Material          | Ceramic Steatite     |
| Contact Material       | Silver Plated Nickel |
| Wire Type              | UL 1659              |
| Wire Gauge (AWG)       | 16 AWG               |
| Wire Color(s)          | Brown, Blue, Green   |
| Lead Strip Length (in) | 0.25 in              |
| Lead Strip Length (mm) | 6.35 mm              |

#### Additional product data

|                                    |              |
|------------------------------------|--------------|
| Lamp Base Reference                | G9.5, Bi-Pin |
| Maximum Operating Temperature (°C) | 250 C        |
| Rohs Compliant                     | Yes          |
| Underwriters Laboratories File No. | E31557       |

### Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 69017          | 4052899016002 | Shipping box (Case) | 10       | 10.1 in x 7.4 in x 3.1 in    | 4 lb         |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.