
TP22XL 36IN16GAULSF2 50/CS 10/SKU



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69006
Product Name	TP22XL 36IN16GAULSF2 50/CS 10/SKU
Ordering Abbreviation	TP22XL 36IN16GAULSF2 50/CS 10/SKU
Brand Name	OSRAM
CSA File No.	LR20904
Old Part Number	F510870

Electrical data

Maximum Wattage (W)	1000 W
Maximum Voltage (V)	250 V

Physical attributes

Length (in)	2.16 in
Length (mm)	54.8 mm
Width (in)	0.85 in
Width (mm)	21.7 mm
Height (in)	1.25 in
Height (mm)	31.8 mm
Body Material	Ceramic Steatite Body / Die Cast Aluminum Housing
Contact Material	Silver Plated Nickel
Wire Type	SF2
Wire Gauge (AWG)	16 AWG
Wire Color(s)	White
Lead Length (in)	36 in
Lead Length (mm)	914 mm
Lead Strip Length (in)	0.375 in
Lead Strip Length (mm)	9 mm

Additional product data

Lamp Base Reference	G9.5, 2-Pin Medium Base
Maximum Operating Temperature (°C)	200 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	E31557

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69006	4008321388735	Shipping box (Case)	10	10.1 in x 7.4 in x 2.4 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.