

HMI 6000W/DXS 1/CS 1/SKU



Product features and benefits

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps $\geq 6000W$
- Mechanically robust with eXtreme Seal (XS) technology, up to 450°C at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- Compression sealed base provides enhanced durability

Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	54315
Product Name	HMI 6000W/DXS 1/CS 1/SKU
Family Brand Name	HMI
Application	Film, TV & Video Production, Studio Lighting, Solar Simulation
Product Remark	<ul style="list-style-type: none">- DXS=Double-ended eXtreme Seal technology- p (Operating Position) = Horizontal- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.

Electrical data

Nominal Wattage	6000 W
Nominal Voltage	122 V
Current (A)	55.0 A
Type of Current	AC

Light technical data

Luminous Flux	570000 lm
Luminous Efficacy (lm/W)	95 lm/W
Light Center Length - LCL (mm)	54 mm
Color Temperature	6000 K
Color Rendering Index	90
Average Rated Life	500 h

Physical attributes

Base	S25.5
Bulb Shape	R54X60/1044
Maximum Overall Length (mm)	450 mm
Length l1 (mm)	450 mm
Length l1 max. (mm)	450 mm
Diameter d (in)	2.126 in
Diameter d (mm)	54.00 mm
Electrode Gap - cold (mm)	21 mm

Additional product data

Operating Position	P 15
--------------------	------

Product datasheet

Maximum Base Temperature (°C)	450 C
Cooling	CONVECTION
Hot Restart	Yes

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54315	4008321210210	Shipping box (Case)	1	25.6 in x 5.6 in x 6.3 in	2.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.