

HSR 575/72 10/CS 1/SKU



Product features and benefits

- Proven, reliable technology for entertainment and architectural fixtures
- Designed with an outer quartz jacket providing compact and rugged construction
- High luminous efficacy of up to 90 lumens/watt

Areas of application

- Concert lighting
- Club & Disco
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54116
Product Name	HSR57572 95V 10/CS 1/SKU
Ordering Abbreviation	HSR 575/72 10/CS 1/SKU
Brand Name	OSRAM
Family Brand Name	HSR
General Description	575 watt, metal halide, single-ended, no hot restart
Application	Entertainment, Effect, and Architectural Lighting

Electrical data

Nominal Wattage	575 W
Nominal Voltage	95 V
Current (A)	7 A
Type of Current	AC

Light technical data

Luminous Flux	49000 lm
Average Luminance (cd/cm ²)	10000 cd/cm ²
Light Center Length - LCL (mm)	65 mm
Color Temperature	7200 K
Color Rendering Index	85
Average Rated Life	1000 h

Physical attributes

Base	GX9,5 Bipin Prefocus
Bulb Shape	T30
Maximum Overall Length (mm)	125 mm
Length l (mm)	125 mm
Diameter d (in)	1.181 in
Diameter d (mm)	30.00 mm
Distance a (mm)	65 mm
Electrode Gap - cold (mm)	7 mm
Reflector Coating	30.00

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	230 C

Product datasheet

Cooling	Convection
Hot Restart	No
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54116	4008321662583	Folding box (SKU)	1	2.2 in x 2.2 in x 6.8 in	0.2 lb
54116	4008321662590	Shipping box (Case)	10	11.6 in x 4.9 in x 7.5 in	3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.