

## HPL 575/240 (UCF)



### Product features and benefits

- Ultra compact filament design (UCF) for high lumen output
- Unique gas fill which improves light output and minimizes risk of arc-out
- Special heat sink base for maximum durability in high temperature applications
- Reinforced pinch seal for extra mechanical strength
- Foam packaging for easier handling and installation
- Optimum system performance with TP22H socket

### Areas of application

- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

## Product datasheet

### Technical data

#### General product information

Product Number	54619
Product Name	HPL575240 (UCF) 240V 12/CS 1/SKU
Ordering Abbreviation	HPL 575/240 (UCF)
Brand Name	OSRAM
Family Brand Name	HPL
General Description	575 watt, tungsten halogen, HPL series

#### Electrical data

Nominal Wattage	575 W
Nominal Voltage	240 V

#### Light technical data

Luminous Flux	14900 lm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h

#### Physical attributes

Base	G9.5 with Heat Sink
Bulb Shape	T6
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Reflector Coating	19.00

#### Additional product data

Total surface inside 1: appearance (cold)	Clear
Lamp Type	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54619	4050300461830	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54619	4050300461847	Shipping box (Case)	12	6.9 in x 5.9 in x 5.3 in	2.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.