

## HPL 375/115 (UCF)



### Product features and benefits

- Ultra compact filament design (UCF) for high lumen output
- Unique top bridgeless construction improves beam uniformity for lamps with  $\leq 120$  volts
- Unique gas fill which improves light output and minimizes risk of arc-out
- Special heat sink base for maximum durability in high temperature applications
- Reinforced pinch seal for extra mechanical strength
- Foam packaging for easier handling and installation
- Optimum system performance with TP22H socket

### Areas of application

- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

## Technical data

### General product information

Product Number	54625
Product Name	HPL375115UCF115V 12/CS 1/SKU
Ordering Abbreviation	HPL 375/115 (UCF)
Brand Name	OSRAM
Family Brand Name	HPL
General Description	375 watt, tungsten halogen, HPL series
Application	Stage & Studio

### Electrical data

Nominal Wattage	375 W
Nominal Voltage	115 V
Type of Current	AC

### Light technical data

Luminous Flux	10540 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	300 h

### Physical attributes

Base	G9.5 with Heat Sink
Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	4-C8
Reflector Coating	19.00

## Product datasheet

### Additional product data

<b>Operating Position</b>	Any
<b>Total surface inside 1: appearance (cold)</b>	Clear
<b>Class</b>	C (gas)
<b>Lamp Type</b>	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54625	0046135546259	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54625	10046135546256	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.