Product family datasheet

OSRAM

LEDriving Curved Lightbar VX1000-CB SR SM




Single mount certified
For individual installation



Up to 525 m long beam
Improved view and visibility
in low light conditions



Combo beamDesigned for both: far-





Curved design

Complements the vehicle's contours giving it a sleek and modern look



Illuminate your path with precision and style

Experience the ultimate lighting solution with our LEDriving Curved Lightbar VX1000-CB SR SM, specifically designed to provide both far-field and near-field illumination. With an impressive power level of 7650 effective lumens and 36 high-performance OSRAM LEDs, this lightbar ensures exceptional visibility up to 525 meters. The stylish curved design complements the contours of your vehicle, giving it a sleek and modern look. Even in dim light and reduced visibility due to external environmental influences, the OSRAM Curved Lightbar with up to 6000 Kelvin can provide conditions similar to daylight. In addition, it is certified for single mounting (2x ECE R149), offers the highest protection classes (IP6K8 & IP6K9K) and features a robust aluminum die-cast housing with a slim, single-row design. The included brackets allow for versatile mounting options on various parts of the vehicle, including curved surfaces like bumpers, grills, and windshields 1). With a 2-year OSRAM guarantee²⁾, this lightbar delivers proven quality and enhanced visibility at an economical price. Discover the perfect combination of performance, design, and versatility with our Curved Lightbar - ideal for those who value top quality and stylish design.

Product family datasheet

Technical data

	Product information	General Product Information		Electrical Data			Photom etric Data
Product description	Application (Category and Product specific)	Global order reference		Nominal wattage		Test voltage	Nominal luminou s flux
LEDriving Curved Lichtbar VX100-CB SR-SM	Driving Light - Additional high beam application - central single mount	LEDDL135-CB SR 108 W 13.2 V 101 lm				10100 lm	
	Lifetime Data	Capabilities	Certific	ates & standard	ls		
Product description	Lifespan Tc	Technology		Approval marks – ECE reference approval number		rence	
LEDriving Curved Lichtbar VX100-CB SR-SM	> 5000 hr	LED	E57 ap	oroval	17.5 + 1	7.5	
	Logistical data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)					
Product description	Commodity code	Candidate list substance 1		CAS No. of substance		Safe use instruction	
LEDriving Curved Lichtbar VX100-CB SR-SM	85122000900	Lead		the C subst suffic safe u		The identi the Candic substance sufficient t safe use of article.	late List is to allow

Product description	Declaration no. in SCIP database
LEDriving Curved Lichtbar VX100-CB	e67db80d-3aab-
SR-SM	4539-83ac-
	000750ed7092

Product family datasheet

Download Data

File



User instruction

LEDriving LEDDL135 Curved Lightbar VX1000-CB SR SM C



User instruction

GPRS_Safety symbols instructions

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.