Product family datasheet

LEDriving SL P21W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Red



Easy upgrade to LED technology with plug & play solutions

Replaces conventional P21W lamps



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product information | | | General Product Information | | Electrical Data | | |
|--------------------------------|---|---|---------|--------------------------------|--------------------------|--------------------------------|-------------------------|-------------------|
| Product description | Product type (off- road vs. on-road) | type (off- and Product specific) road vs. | | Global order reference | | Power Nominal voltage input | | voltage |
| LEDriving SL \triangleq P21W | Off-road ≙ P21W | Mainly used signal/ indic applications | ator | 7506DRF |) | 1.8 W | 12 V | |
| | | | | | Photometric | Data | Physical A Dimensior | ttributes & 15 |
| Product description | Nominal watt | in | | Test voltage | Nominal luminous flux | | Lamp base | |
| LEDriving SL \triangleq P21W | 1 W | ±2 | 25 % | 13.5 V | 100 lm | | BA15s | |
| | | | | | | | Lifetime D | Jata |
| Product description | Length | Di | iameter | | Diameter | | Lifespan B3 | Lifespan Tc |
| LEDriving SL \triangleq P21W | 52.5 mm | 2! | 5.0 mm | | 25.0 mm | | 1500 hr | 4000 hr |
| | Capabilities | Capabilities Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 190 (REACh) | | | | | 7/2006 | |
| Product description | Technology | Primary ar identifier | ticle | Candidate list substance 1 | | CAS No. of substance 1 | | ce |
| LEDriving SL \triangleq P21W | LED ¹⁾ | 40621724 | | Lead | 7439 | | 92-1 | |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|---------------------|---|--|
| LEDriving SL ≙ P21W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 5271a66b-2494- 48e0-aef0- f73e7dcb0bfc |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

| File |
|---|
| User instruction GPRS_Safety symbols instructions |
| Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.