Product family datasheet

LEDriving SL P27/7W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Red




Easy upgrade to LED technology with plug & play solutions

Replaces conventional P27/7W lamps



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

OSRAM

Product family datasheet

Technical data

Product type (off-	••	on (Category					Electrical Data	
road vs. on-road)	Application (Category and Product specific)		-	Global order reference		Nominal	voltage	
Off-road ≙ P27/7W	signal/ in	ndicator	3157DR	P	1.8 W	12 V		
				Photometric	Data	-	ttributes & 15	
Nominal watt	age	Power input toleranc e	Test voltage	Nominal luminous flux		Lamp base	<u>.</u>	
1 W		±25 %	13.5 V	60/10 lm		W2.5x16q		
						Lifetime D	ata	
Length		Diameter		Diameter		Lifespan B3	Lifespan Tc	
49.0 mm		25.7 mm		25.7 mm		1500 hr	4000 hr	
	P27/7W Nominal watt	P27/7W signal/ ir applicati Nominal wattage	P27/7W signal/ indicator applications Nominal wattage Power input toleranc e 1 W ±25 % Length Diameter	P27/7W signal/ indicator applications Nominal wattage Power input toleranc e Test voltage toleranc e 1 W ±25 % 13.5 V	P27/7W signal/ indicator applications Nominal wattage Power input toleranc e 1 W ±25 % 13.5 V 60/10 lm	P27/7W signal/ indicator applications P27/7W signal/ indicator applications Photometric Data Photometric Data Nominal wattage Power input toleranc e Nominal luminous flux 1 W ±25 % 13.5 V 60/10 lm Length Diameter Diameter	P27/7W signal/ indicator applications Photometric Data Physical A Dimension Nominal wattage Power input toleranc e Nominal luminous flux Lamp base 1 W ±25 % 13.5 V 60/10 lm W2.5x16q Length Diameter Diameter Diameter Lifetime Diameter	

		(REACh)			
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1	
LEDriving SL ≙ P27/7W	LED ¹⁾	4062172151689 4062172401777	Lead	7439-92-1	

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≜ P27/7W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a5c512b0-7fa2- 4907-bc1f- 816fe7f2d8ed

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.