## **OSRAM**

# **LEDriving SL P13W**

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P13W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for P13W

LEDriving SL P13W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P13W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Product family datasheet

#### Technical data

	Product information		Genera Informa	l Product ation	Electrical D	ata
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global referen		Power input	Nominal voltage
LEDriving SL ≜ P13W	Mainly used for daytime running light applications	Off-road ≙ P13W	828DW	Р	1.90 W	12 V
			Photometric Data			Physical Attributes & Dimensions
Product description	Nominal wattage	Test voltage	Nominal flux	luminous	Luminous flux tolerance	Diameter
Product description  LEDriving SL	Nominal wattage			luminous	flux	Diameter 23.0 mm

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≙ P13W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5d297eba-e23a- 4652-864d- 445415f98c63   86a80c4c-80ba- 4d88-b8fd- 60cafbfef775

Lifespan

1500 hr

Lifespan

4000 hr

Tc

Technology

LED 1)

Primary article identifier

4062172401432 | 4062172150279

Diameter

23.0 mm

**Product description** 

 $<sup>^{1)}</sup>$  Light-emitting diode lamp

#### Product family datasheet

#### Download Data

#### File



User instruction

GPRS\_Safety symbols instructions



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

#### Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.