

# LEDiving HLM EASY GEN 2 H4/H19



**Ultra compact LED replacement for conventional H4/H19 high and low beam lamps**

“Socket Design” – no adapters and caps needed



**Easy plug & play installation**

Allowing a high compatibility and an easy installation



**Cool White color temperature**

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDiving HLM EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional H4/H19 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDiving HLM EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description               | Electrical Data  |                 |                 | Photometric Data      |                         |
|-----------------------------------|------------------|-----------------|-----------------|-----------------------|-------------------------|
|                                   | Power input      | Nominal voltage | Nominal wattage | Nominal luminous flux | Luminous flux tolerance |
| LEDDriving HL EASY GEN 2 ≙ H4/H19 | 16.5W/1<br>6.5 W | 12 V            | 22 W            | 1850/1500 lm          | ±25 %                   |

| Product description               | Physical Attributes & Dimensions | Lifetime Data | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                  |
|-----------------------------------|----------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------|
|                                   | Diameter                         | Lifespan Tc   | Primary article identifier                                                                                      | Declaration no. in SCIP database |
| LEDDriving HL EASY GEN 2 ≙ H4/H19 | 21.5 mm                          | 1000 hr       | 4062172420327                                                                                                   | In work                          |

Download Data

| File                                                                              |                                                           |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------|
|  | User instruction<br>GPRS_Safety symbols instructions      |
|  | Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.